

Accelerate your digital transformation journey

fi-8270

Made for demanding workflows, the Fujitsu fi-8270 employs innovative feeding and Clear Image Capture technology to deliver industry-leading reliability. The flatbed provides even more utility, making it possible to scan very thick documents and bound periodicals.



Image Quality

Clear Image Capture (CIC) technology resets the benchmark for high quality image capture, by combining the reliability and flexibility of Contact Imaging Sensor (CIS) hardware, with an industry-leading, image processor. CIC technology delivers precise, crisp images, and industry-leading OCR accuracy rates while also removing unwanted watermarks and artifacts.

Paper Feeding

Evolved paper handling with a large 100-page hopper, an all-wheel drive mechanism, and fast 140 images captured per minute, make the fi-8270 one of the easiest and most efficient scanners to operate. The patented Automatic Separation Control uses state of the art technology to sense paper weights and adjusts to consistently separate documents and provide the perfect feed, ensuring documents are safely captured.

Reliability

The fi-8270 is built to last and powers up every time you need it regardless of job size. Strong urethane rollers, heavy duty motors, a sturdy frame, and durable consumables combine for a long-lasting scanner that will let your organization capture the volumes of paper from seasonal peaks and heavy backlogs, worry free. Backed by Fujitsu's US-based, legendary solutions architects and support teams.



PaperStream IP

Compatible with all major document management software packages, PaperStream IP (PSIP) is a TWAIN/ ISIS® compliant driver that cleansup and optimizes scanned images without any configuration.

PaperStream Capture

Take advantage of powerful indexing and sorting features, putting the document in the right location for great organization and fast retrieval. Now includes both 2D and 1D barcode support in the box.

PaperStream Clickscan

Easy to use capture software for any business. Simple scanning interface with 3-steps: scan, select destination, and save.

Flexible connectivity options

Choose between PaperStream IP Net for flexible, adaptable capture architectures, and PaperStream NX Manager for centralized, serverbased capture.



The next generation in scanning excellence Fujitsu fi-8270 Image Scanner



Power Consumption Operating Mode

Auto Standby (Off) Mode

Operating Environment

Environmental Compliance

Sleep Mode

Temperature

Dimensions*1 (Width x Depth x Height)

Supported Operating

Included Software / Drivers

Image Processing

Included Items

Trade Compliant

Functions

Weight

System

Relative Humidity





0.2 W or less

41 to 95 °F (5 to 35 °C)

ENERGY STAR®, RoHS

19.4 lb (8.8 kg)

15 to 80% (non-condensing)



28 W or less / 17 W (Eco mode)

2.0 W or less (LAN) / 1.4 W or less (USB)

11.8 x 22.7 x 9.2 in. (300 x 577 x 234 mm)

Windows® 11, Windows® 10, Windows® 8.1, Windows® 7,

Windows Server® 2022, Windows Server® 2019, Windows

Server® 2012, Windows Server® 2008 R2, macOS, Linux

PaperStream Capture, PaperStream ClickScan*17, Software

Operation Panel, Error Recovery Guide, ABBYY FineReader for ScanSnap™*17, Scanner Central Admin

Multi image output, Automatic color detection, Blank page detection, Dynamic threshold (iDTC), Advanced

DTC, SDTC, Error diffusion, Dither, De-Screen, Emphasis,

Dropout color (None/Red/Green/Blue/White/Saturation/

Custom), sRGB output, Hole punch removal, Index tab cropping, Split image, De-Skew, Edge filler, Vertical

streaks reduction, Background pattern removal,

ADF paper chute, AC cable, AC adapter, USB cable,

Server® 2016, Windows Server® 2012 R2, Windows

PaperStream IP Driver (TWAIN/TWAIN x64/ISIS), WIA Driver*16, Image Scanner Driver for Linux (SANE)*16*17







Technical Information

Scanner Type

Scanning Speed*1

(A4 Portrait) (Color / Grayscale*2 / Monochrome*3)

Image Sensor Type

Light Source

Optical Resolution Output Resolution*

(Color / Grayscale / Monochrome)

Output Format Background Colors

Document Size Maximum*6 ADF Minimum

Long Page Scanning*7 Flatbed Maximum

Paper Weight (Thickness)

Paper Booklet Plastic Card

ADF Capacity*11 *12

Expected Daily Volume*13

Multifeed Detection

Paper Protection

Interface

Ethernet

Consumables

Black Document Pad

Service Programs & Options 1 Year Advance Exchange

Power Requirements

3 Year Advance Exchange Depot Mail-in Repair

ADF (Automatic Document Feeder) / Manual Feed,

Simplex: 70 ppm (200/300 dpi) Duplex: 140 ipm (200/300 dpi Flathed 1.7 seconds (200/300dpi)

CIS x 2 (front x 1, back x 1) Flatbed: Color CCD x1

ADF: RGB LED x 2 (front x 1, back x 1)

Flatbed: White LED

ADF

50 to 600 dpi (adjustable by 1 dpi increments)

1,200 dpi (driver)*5

Color: 24-bit, Grayscale: 8-bit, Monochrome: 1-bit

White/Black (selectable) Flatbed: WHite (or optional black)

8.5 x 14 in. (215.9 x 355.6 mm) 1.9 x 2 in. (48x50 mm) 240 in. (6,096 mm)

8.5 x 11.7 inch (215.9 x 297 mm)

5.3 to 124 lb (20 to 465 g/m²)*8 0.276 in. (Less than 7 mm)*

0.055 in. (1.4 mm) or less*10 100 sheets (Letter 20 lb or A4 80 g/m²)

10,000 sheets

Overlap detection (Ultrasonic sensor)

Length detection

Image monitoring, Sound detection (iSOP)*14

3.2 Gen 1x1 / USB 2.0 / USB 1.1 10BASE-T, 100BASE-TX, 1000BASE-T

AC 100V to 240V 50/60Hz

Additional service coverage durations and response times at fujitsuscannerstore.com/service_programs

S8270-AEPWNBD-1 S8270-AEMYNBD-3 S8270-DEPW5DY-3

spare parts, labor, and one-way shipping to customer

Black back flatbed cover for cropping

replacement for scanner equipment* 3-year scanner contract provides mail-in unit repair that includes

Fujitsu industry-leading support keeps digital transformation projects on-time and on budget One or three year program offers whole-unit, next business day

· U.S. based support

Cropping, Static threshold.

Setup DVD-ROM

Specialized Teams

• Flexible service programs

Genuine Fujitsu Consumables are available at fujitsuscannerstore.com

Brake Roller PA03810-0001 Lifetime: approx. 200,000 sheets or 1 year Pick Roller PA03670-0002 Lifetime: approx. 200,000 sheets or 1 year ScanAid Kit CG01000-302801 Consumable kit with instructions and cleaning supplies Booklet Carrier (1Piece) PA03810-0020 Supplemental protection for items such as passports Carrier Sheets (5 Pieces) PA03360-0013 Supplemental protection for delicate items

PA03810-D301









*1 Actual scanning speeds may vary with data transmission and software processing times. *2 Indicated speeds are from using JPEG compression. *3 Indicated speeds are from using TIFF CCITT Group 4 compression. *4 Selectable maximum resolution may vary depending on the length of the scanned document. *5 Limitations may apply to the size of documents that can be scanned, depending on system environment, when scanning at high resolution (over 600 dpi). *6 Maximum document width possible for scanning is 240 mm (9.5 inch). *7 For use with PaperStream NX Manager, the maximum resolution supported is 400 dpi, with maximum lengths ranging with resolution. Simplex: 1,828.8 mm (72 in.) [below 300 dpi], 355.6 mm (14 in.) [below 400 dpi]. *8 Thicknesses of up to 128 to 209 gmiz (34 to 56 lb) can be scanned for A8 (52 x 74 mm / 2.1 x 2.9 inch) sizes. *9 Indicated thickness is inclusive of Booklet Carrier Sheet thickness when using the Carrier Sheets. *10 Continuous feeding is supported when scanning up to 10 unembossed cards with thicknesses of 0.7.6 mm or less. *11 Maximum capacity depends on paper weight and may vary. *12 Capable of setting additional documents while scanning. *13 Numbers are calculated using scanning speeds and typical hours of scanner use, and are not meant to guarantee daily volume or unit functions (paper Protection. *15 Excludes the ABT) paper chuse and stare. *16 Functions equivalent to those offered by PaperStream IP may not be available with the Image Scanner Driver for Linux or WIA Driver. *17 Refer to the fi Series Support Site for driver/software downloads and full lineup of all supported operating system versions. https://www.fujitsu.com/olabals/support/indur/str/cymum/tra/cymum/tr global/support/products/computing/peripheral/scanners/fi/.

ISIS is a trademark of Open Text. Microsoft, Windows, and Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Linux is the registered trademark of Linus Torvalds in the U.S. and other countries. Any other products or company names appearing in this document are the trademarks or registered trademarks of the respective companies.

Safety Precautions

Please carefully read the safety precautions prior to the use of this device and follow the recommended instructions for correct use. Do not place this device in wet, moist, highly humid, dusty or oily areas. Use of this device under such conditions may result in electrical shock, fire or damage to the device. Please use this device within the power ratings listed.

PFU Limited, a Fujitsu company, has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR® is a registered trademark of the United States Specifications are subject to change without notice.

